

STANDARD FEATURES

- 1 - Flexible Rubber Clean-up Hose7" x 8' (18 cm x 2.4 m)
- 2 - Stainless Steel Flexible Hoses.....7" x 8' (18 cm x 2.4 m)
- 1 - Stainless Steel Flexible Hose7" x 3' (18 cm x 0.9 m)
- 1 - Aluminum Pipe7" x 5' (18 cm x 1.5 m)
- 2 - Aluminum Pipe7" x 8' (18 cm x 2.4 m)
- 1 - Aluminum Bin Load-out Nozzle.....7" x 3' (18 cm x 0.9 m)
- 1 - Floor Sweep With Handles.....7" x 4' (18 cm x 1.2 m)
- 1 - Clean Up Nozzle With Wheels7" (18 cm)
- Inspection Window5" (13 cm)
- Pressure Relief Slide
- Trailer Tires ST205/75R15
- Rubber Torsion Axle – smoother riding/highway towing speeds
- 1000 PTO Shaft
- Hour Meter & Tachometer
- Easy Access Lower Auger Clean Out Door
- Tough Powder Coat Finish
- Poly Wear Liners in High-Abrasion Areas
- Heavy Duty Gear Box & Drive Line Components
- Hard Surfaced Flyting
- Brush Kit
- Built-in Telescoping Inlet
- NEW! Modular Exhaust System
- NEW! Auger Hinges - greaseless
- NEW! Storage Location for Nozzles
- NEW! Heavy-Duty Auger Bearing Mounts
- NEW! High Flow Discharge

Due to continuing research and development on design and manufacturing procedures, technical data and specifications are subject to change without notice.

SPECIFICATIONS

Transport Position

- Width94 13/16" (241 cm)
- Height (with exhaust on).....106 3/4" (271 cm)
- Height (with exhaust off)78 1/2" (199 cm)
- Weight2800 lbs. (1270 kg)
- Hitch Weight400 lbs. (181 kg)

During Operation

- Discharge Auger 10" (25 cm)
- Auger Extension.....Angle 45 degree
- Auger Discharge Height 192" (4.57 m)
- Height 106 3/4" (271 cm)
- Inlet Height (from ground)28 1/2" (73 cm)
- Rubber Torsion Axle Width..... 112" (285 cm)

Minimum Hydraulic Requirement: 2 GPM flow rate @ 2100 PSI
 Minimum Tractor Requirement: 70 horsepower at 1000 PTO rpm



Canadian & USA Patents Pending



Rem Enterprises Inc.
 2180 Oman Drive
 Swift Current, SK Canada
 S9H 3X4


Phone 306.773.0644
 Fax 306.773.1188
www.rementerprisesinc.com
remsales@rem.sk.ca

1-800-667-7420

Excellent for...



Barley



Canola



Corn



Durum



Oats



Peas



Soy Beans



Spring Wheat



Sun Flower

Grain VAC ^{FASTEST IN THE FIELD!} 27 *hundred*



55' (16.8m) of hose provided with every machine

Equipped with floor sweep with long handles & clean up nozzle on wheels

16' (4.9m) of auger clearance

Rugged Reliable... Rem

1-800-667-7420

GET TO THE FINISH LINE **FIRST**

6,000 BUSHEL/HOUR (218 MT/HR) AT FULL BIN LOAD-OUT - THE PEAK IN EFFICIENCY!

NEW REM **GRAIN VAC 2700**: WE'VE MADE THE BEST VAC EVEN BETTER!

NEW

LOWER NOISE

- Specially engineered airflow technology dramatically reduces the noise volume and pitch

NEW

HEAVY-DUTY AUGER BEARING MOUNTS

- The middle auger bearing mounts are heavy-duty to support the weight of the auger and the material moving through during operation
- Auger bearing mounts are a single leg bearing support

NEW

"LOCKED IN PLACE" ROTOR ASSEMBLY

- Rotors come locked in the proper position from the factory
- Rotor is held in place with a lock nut
- When you have to replace the rotor or bearings there is no need to make adjustments to get the proper clearance between the rotor and the inlet plate
- This design allows the rotor assembly to only be in one place

NEW

UNIQUE AUGER DESIGN

- Fold and unfold adjacent to the bin
- 10" discharge
- 16' clearance
- Protected upper auger bearing

NEW

HASSLE FREE MACHINED FIT

- Hassle free machined fit between the rotary screen and rotor inlet plate
- No more seals to replace between screen and fan

NEW

MODULAR DIRECTIONAL EXHAUST

- Swivel action allows you to adjust the exhaust direction
- Modular components - purchase optional components to adjust the direction & the length of the exhaust

NEW

REAR IDLER ASSEMBLY

- Engineered for fewer moving parts and less maintenance

NEW

HIGH FLOW DISCHARGE

- Single door allows for tighter air seal

CAPACITY

Testing shows that results may vary based on conditions:

- Up to 6,000 bu/hr during full bin load-out
- Hose configuration is important for optimizing maximum capacity: use the stainless steel flex hoses and aluminum pipes first and the flexible rubber hose when necessary
- Use the bin load out nozzle for full bin load-out, and the floor sweep or vac nozzle for final clean up operations

RUBBER TORSION AXLE

- Reduce vibration during operation
- Smoother towing at highway speeds

TACHOMETER & HOUR METER

- Monitor the hours the GrainVAC has operated
- To ensure the PTO is running at recommended speed

WARRANTY

Rem Enterprises Inc. will guarantee each new 2700 GrainVAC to be free from factory defects in material and workmanship for 2 years from the date of delivery by the dealer to the original purchaser.

- Certain exclusions may apply
- Details are included in the operator's manual

SEED QUALITY

- Independent tests by grain elevators indicate that the Rem GrainVAC causes less damage to valuable seed than conventional vacuum systems where high speed airlocks are used
- The unique drum and exhaust design separates dust and foreign matter from the grain, thereby improving the quality of the material that you deliver

EFFICIENCY

Rem's design team believes in helping you get the best for your money, effort and horsepower.

PARTS & SERVICE


Rem is very proud of its dealers and representatives throughout North America, Australia, New Zealand, and Europe. We stock replacement parts in Canada, the United States, Australia, and France to provide fast service and our factory team is standing by to support all Rem products.

HEALTH & SAFETY

- The Rem GrainVAC promotes a dust free environment in the bin and eliminates dangerous open augers
- The design provides safe access for servicing and part replacement
- All aspects of GrainVAC operation have been tested, inspected and safety approved

PROVEN DESIGN MEANS LOW MAINTENANCE

- The Rem GrainVac system is patented
- High speed rotor bearings
- High tech design of this machine naturally lends itself to low maintenance



One Person Set-up & Operation



Compact Transport Configuration

6,000 BUSHEL PER HOUR